KoubaLink Installation Instructions

Fits: 1994-up Kawasaki KLX250/300 & KLX250 dual sport. (PN. KLX2, KLX3 & KLX4)

- 1) Raise the motorcycle with a bike stand, milk crate, etc., so the rear wheel is just slightly off the ground. Remove the two 17 mm nuts from the bolts that hold the links to the rocker and swing arm. You may have to remove the lower chain roller and the screw holding the bottom of the rubber swing arm protector to allow the link bolts to be removed out the left side. (Raise the rear wheel slightly to allow the first bolt to slide out easily)
- 2) After removing the stock links you should be ready to install the KoubaLinks, (engraving to the outside) this time push the link bolts in, starting from the right side. Install the link mounting bolt nuts and torque to 40 lb-ft.
- 3) For the best performance set the sag (amount of vertical movement of the rear axle FROM no weight to bike weight plus rider weight) at 3 1/2" with the KLX2 links, 3 1/4" with the KLX3 links, and 3" with the KLX4 links. Sag is measured with the rider in full riding gear, standing on the pegs, and including all carried items. If the links are for lowering purposes ONLY, sag is set at 3.90 inches, and will lower the rear of the bike .75 inch with the KLX2 links, 1.25 inches with the KLX3 links, and 1.75 inches with the KLX4 links. *Each length link lowers the 09-up KLX250 1/4" less.
- 4) The front forks can be slid up in the triple clamps .5" until they almost contact the handlebars. For additional lowering of the front, a second set of the top handlebar clamps can be installed under the bars and tightened with 3/4" longer bolts, that will allow the forks to be slid up an additional 3/4"inches.

*Disclaimer: Raising or lowering the rear more than the front can change the geometry and could affect the handling, so be careful out there.

If you like what the KoubaLinks do for your suspension, please tell everyone, if you do not, please tell us. We can be contacted at our e-mail address below and are always interested in your questions or comments.